

OTHER DEVICES

EXCIMER LASERS

Company Name	Product	Product Description	Configuration	Working Length (cm)	Comments
Spectranetics Corporation	Turbo Elite Laser Ablation Catheters for Peripheral Intervention	.9 mm X-80 catheter	OTW	150	Spectranetics' Turbo Elite laser ablation catheters are for use in the endovascular treatment of symptomatic, infrainguinal, lower-extremity, vascular disease where total obstructions cannot be crossed with standard guidewires.
		.9 mm X-80 catheter	RX	150	
		1.4 mm catheter	OTW	150	
		1.4 mm catheter	RX	150	
		1.7 mm catheter	OTW	150	
		1.7 mm catheter	RX	150	
		2 mm catheter	OTW	150	
		2 mm catheter	RX	150	
		2.3 mm catheter	OTW	120	
		2.5 mm catheter	OTW	110	

Recommended Calibration Settings: 45 Fluence, 25 Hz; CVX-300 Excimer Laser Ablation System software upgrade required
OTW=Over-the-Wire; RX=Rapid Exchange

GUIDEWIRES (PRESSURE WIRES) - COILED STAINLESS STEEL

Company Name	Product Name	Type (Fixed Core or Movable Core)	Diameter (inch)	Length (cm)	Tip Type	Anti-Thrombogenic (Yes/No)	Comments
Radi Medical Systems, Inc.	PressureWire	Fixed core	.014	175, 300	Straight	Yes, PTFE coated	Ability to measure pressure, flow, and temperature on one guidewire.

PLAQUE EXCISION

Company Name	Product Name	Minimum Vessel Diameter (mm)	Sheath Compatibility (F)	Crossing Profile (inch)	Working Length (cm)	Tip Length (cm)
FoxHollow Technologies, Inc.	SilverHawk LS-F	4.5	7, 8	.105 (2.7 mm)	107	6
	SilverHawk MS-F	3.5	7, 8	.105 (2.7 mm)	107	6
	SilverHawk LX	4.5	7, 8	.105 (2.7 mm)	113	9
	SilverHawk LS	4.5	7, 8	.105 (2.7 mm)	110	6
	SilverHawk MS	3.5	7, 8	.105 (2.7 mm)	110	6
	SilverHawk SX	3	7	.095 (2.4 mm)	136	4.3
	SilverHawk SS+	3	7	.090 (2.3 mm)	135	2.6
	SilverHawk ES+	2	6	.075 (1.9 mm)	135	2.2
	SilverHawk DS	1.5	6	.062 (1.57 mm)	135	2.6